



Product data sheet

LOUI 50
925328.0045.1.76
RZB



Series: Less is more 50 Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Available Colours: white aluminium (RAL 9006) Type of Installation: Pendant Dimensions: L 1961, B 57, H 75 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 5650lm System power: 47W Beam Angle: 106° Number of fittings B10A: 15 Number of fittings B16A: 24 Number of fittings C10A: 24 Number of fittings C16A: 40 Inrush current: 24,9A Unified Glare Ratio: 26,3 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	47 W	CRI	80
Total flux	5650 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	47 W

Mounting mode

Wall mounted

Shape and measurements

Length: 2.24 in
Width: 77.17 in
Height: 2.95 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 47 W

Protection

IP: 20
IK: 02