Product data sheet

LINEDO_4,5M_AD_11111111
9545AD.850.400.002
RZB



IP 54 IK 03

LINEDO, 167 W, 25200 lm, 850, aluminium, on/off Continuous line luminaire, L 4547 B 58 H 76

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	20.88 W	CRI	80
Total flux	3150 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	20.88 W

Light output 2 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	20.88 W	CRI	80
Total flux	3150 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	20.88 W

Light output 3 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	20.88 W	CRI	80
Total flux	3150 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	20.88 W

Light output 4 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	20.88 W	CRI	80
Total flux	3150 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	20.88 W

Light output 5 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	20.88 W	CRI	80
Total flux	3150 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	20.88 W

Light output 6 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	20.88 W	CRI	80
Total flux	3150 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	20.88 W

Light output 7 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	20.88 W	CRI	80
Total flux	3150 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	20.88 W

Light output 8 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	20.88 W	CRI	80
Total flux	3150 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	20.88 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 179.02 in
Height: 2.99 in

Adjustability

Fixed

Electric

System power: 167.04 W

Protection

IP: 54
IK: 03