Product data sheet

SINUS SUSP. 'Y' DI/ID SILVER PRISM. 1174MM
R33Y117-9006E2930L1M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40

low output LED 3000K CRI 90 85,6W 10129lm¹ ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 13,2% https://katalog.planlicht.com/en-gb/fam-sinus/

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.7 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	10.7 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.7 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	10.7 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.7 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	10.7 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.7 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	10.7 W

Light output 5 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.7 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	10.7 W

Light output 6 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.7 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	10.7 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.7 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	10.7 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.7 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	10.7 W

Mounting mode

Pendant

Shape and measurements

Length: 46.22 in
Width: 46.22 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 85.6 W

Protection

IP: 40