



Product data sheet

1570 CLIMA - LED 4000K CRI 70 49W CLD GRAPHITE
422401-56
DISANO



Housing: in die-cast aluminium, top cover in aluminium. Attachment: suited for poles with a diameter of 60 mm. Diffuser: in anti-glare polycarbonate, shatterproof and V2 self-extinguishing, UV stabilised, externally smooth and dustproof. Coating: pre-treatment of metal surface, polyester powder coating to ensure resistance to corrosion and salt spray fogs, UV stabilised. Special coating: upon request: available with coating tested to withstand corrosion tests in aggressive artificial atmospheres (UNI EN ISO 9227) or marine environments (sea front). Heat Sink: built-in. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: - IP67 quick connector. - anti-condensation valve. - temperature controller with auto-reset. - EN 61547 compliant surge protection. - BASIC PROG built-in functions. Mounting: on 60 mm diameter pole or bracket.

Light output 1



1 x LED			
Nominal lamp power	49 W	LOR	100%
Lamp flux	5539 lm	ULOR	5%
Luminous efficacy	113 lm/W	Total flux	5539 lm
CCT	4000 K	Total power	49 W
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 20.24 in

Width: 20.24 in

Height: 16.81 in

Adjustability

Fixed

Design

Material impression: Aluminum

Color of housing: Anthracite / graphite

Electric

System power: 49 W

Appliance Class: II

Protection

IP: 65

IK: 08

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...104°F