Product data sheet

SMART CAKE 82 IP55 LED GE 3000K FLOOD WHITE STRUC 12412409


MODULAR







Smart lighting family Smart Cake, Smart Lotis and Smart Kup form a new generation of spotlights which combine technical ingenuity with timeless design. This family's styling is based on our most popular designs. In concrete terms, the fittings consist of a module which can be combined with one of three trims to suit your requirements. The new spotlights can be combined with Smart Mask to form the perfect solution for any interior. What you get is a LED module with a different finish. The light flows over the edges of the Smart Cake like its bigger sister.

Light output 1







Mounting mode

Ceiling recessed

1 x LED			
Nominal lamp power	13.4 W	LOR	79%
Lamp flux	994 lm	Total flux	790 lm
Luminous efficacy	59 lm/W	Total power	13.4 W
CCT	3000 K		
CRI	90		
1 x LED			
Nominal lamp power	6.2 W	LOR	79%
Lamp flux	576 lm	Total flux	458 lm
Luminous efficacy	74 lm/W	Total power	6.2 W
CCT	3000 K		
CRI	90		
1 x LED			
Nominal lamp power	9.2 W	LOR	79%
Lamp flux	773 lm	Total flux	614 lm
Luminous efficacy	67 lm/W	Total power	9.2 W
CCT	3000 K		
CRI	90		

Shape and measurements

Height: 0.39 in Diameter: 3.23 in

Adjustability

Fixed

Electric

System power: 6.2-13.4 W Appliance Class: II

Protection

IP: 55