


Product data sheet

LOUI 50
925364.003.1.76
RZB




IP
20

IK
03

Series: LESS IS MORE 50system Gerades Einbaumodulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem für Montage in Zwischendecken oder Leichtbau-Hohlwände. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Alea Optik System: Reflektorstruktur (ABS, Aluminium bedampft, hochglänzend) mit Diffusor aus vergilbungsfreiem Kunststoff (PMMA) opal für blendfreies Licht am Arbeitsplatz (UGR <19, Bildschirmgerecht gemäß DIN EN 12464-1). Colour: deep black, matt (RAL9005) Length: 1961mm Width: 71mm Height: 1.5mm Cut-out length: 1968mm Cut-out width: 60mm Recess height: 100mm Luminaire: recess height: 75mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 48W Rated luminous flux: 6200lm Luminous efficiency: 129lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	48 W	CRI	80
Total flux	6200 lm	LOR	100%
Luminous efficacy	129 lm/W	Total power	48 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.80 in
Width: 77.20 in
Height: 0.08 in

Adjustability

Fixed

Electric

System power: 48 W

Protection

IP: 20
IK: 03