Product data sheet

2.5W 3000K 120°
L372-L300
MP LIGHTING



IP 66

Application Exterior/Interior directional in-grade luminaire for lighting walls, columns, architectural features or landscape features. Applicable for mounting into floors, walls, ceilings or other surfaces where a non-obtrusive luminaire is required. Suitable for walk-over and drive-over applications up to 5,500 Kg (12,000lbs). For wet and dry locations. IP Rating 66 Mounting Comes with splice box, aluminum flange and level gauge. Designed to be cast into concrete or inserted into paving stone. Includes 6" wire lead. Can be used with Single Gang Box 2 (not included, can be purchased separately from MP Factory) Electrical Powered by remote dimmable/ non-dimmable driver (sold separately). *See website for recommended drivers *Remote emergency driver / inverter options available. Consult factory. Power Consumption 1.5 Watt (at 350 mA, 1.0 Watt) 3.0 Watt (at 700 mA, 2.5 Watt) Light Output 1.0 Watt, 29~33lm 2.5 Watt, 47~53lm Warranty 5 years limited warranty Estimated useful life of LED is 50,000 hours. Material Solid anodized aluminum or stainless steel (316) with tempered glass lens, RoHS compliant. Weight 1.8lbs (0.816kg) base extra

Light output 1



1 x LED

Nominal lamp power	2 W	LOR	41%
Lamp flux	47 lm	ULOR	41%
Luminous efficacy	8 lm/W	Total flux	19 lm
CCT	3000 K	Total power	2.5 W
CRI	80		

Mounting mode

Floor recessed

Shape and measurements

Length: 1.72 in
Width: 1.72 in
Height: 0.08 in

Adjustability

Fixed

Electric

System power: 2.5 W

Protection

IP: 66