

# Product data sheet


RBXS L40  
RUBIX LED SURFACE  
DEXTRA



IP  
20

Rubix Surface - 600x600 Surface mounted luminaire, white powder coated steel body, individual cells with opal surround trim for precise optical control. Individually switched diffused back lit halo. Options: E3 - Emergency control gear (498 lumens output) ST3 - Emergency control gear self test AT3 - Emergency control gear DALI auto test S - Switch Dimming (2x drivers) D - Digital Dimming (DSI) (2x drivers) A - Digital Addressable Lighting Interface (DALI)(2x drivers) H - High Frequency Dimming (Analogue 1-10v)(2x drivers) R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless occupancy and daylight dimming RLS - Reacta-Link Wireless Presence & Daylight Sensor RCS - Reacta-Control Wireless, Presence BL - Blue Cell Surround OR - Orange Cell Surround R - Red Cell Surround BK - Black Cell Surround

## Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	26.3 W	CRI	80
Total flux	3406 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	4%
		Total power	26.3 W

## Mounting mode

Ceiling mounted

## Electric

System power: 26.3 W

## Shape and measurements

Length: 23.43 in

Width: 23.43 in

Height: 1.57 in

## Protection

IP: 20

## Adjustability

Fixed