


Product data sheet

TENTEC ACCENT RECESSED LUMINAIRE
TL2101503-33-30_11W
SCHMITZ | WILA



Tentec accent LED 3000 K Recessed Luminaire, Light distribution direct Downlight Product: TL2101503-33-30 Operating technology: independent driver required Light Technique CRI > 80 high chromaticity stability with 3SDCM (initial) beam angles $\alpha = 20^\circ, 40^\circ$ or 60° constant colour temperature 3000 K lifetime 50.000 h (L70) Aluminium reflector (Al99.98), high-polished Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised frame thickness of only 2 mm for homogeneous appearance in the ceiling frame colour white, RAL 9016 Operating and assembly technology LED driver to be ordered separately Driver suitable for connection to central battery systems Quick installation due to 2-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 11 W Colour Rendering Index: 80 Colour Temperature: 3000 K Luminaire Luminous Flux: 1190 Lm System Efficiency: 92 Lm/W Half-peak Divergence $\alpha: 60^\circ$ Number Luminaires LZ: 0.10 Connector: screw connector, 2 x 1.5 mm² Reflector Size: Q08 Length: 102 mm Width: 102 mm Cut-out length: 95 mm Cut-out width: 95 mm Installation Depth RD: 105 mm Total Weight: 0.4 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record TL2101503-33-30_11W

Light output 1



1 x General service incandescent lamp

Nominal lamp power	13 W	LOR	100%
Lamp flux	1190 lm	Total flux	1190 lm
Luminous efficacy	92 lm/W	Total power	13 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.02 in

Width: 4.02 in

Height: 4.13 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 13 W

Appliance Class: II

Protection

IP: 20