


Product data sheet

PLATO PRISMA 3K MED DEKORPLÅT CIRKEL SAMT RAM FÖR UTV MONTAGE
E7018675 + E7015894 + E7940002
CARDI




Plato är en infälld armatur i slimmad design, enbart 9,5 mm hög. Stomme av vitlackerad stålplåt, bländskydd av symmetrisk prisma för visuell ljuskomfort. Monteras i undertak med synlig T-profil 600x600 mm. Ställbart ljusflöde via dip-switchar direkt på drivdonet. Levereras med 2 m 2x0,75 mm² anslutningsledning och stickpropp. Plato kan enkelt kompletteras med olika tillbehör som dekorplåtar vilket förändrar armaturens karaktär.


Light output 1



1 x LED			
Nominal lamp power	41 W	LOR	100%
Lamp flux	3326 lm	ULOR	7%
Luminous efficacy	81 lm/W	Total flux	3326 lm
CCT	3000 K	Total power	41 W
CRI	80		



1 x LED			
Nominal lamp power	22 W	LOR	100%
Lamp flux	1858 lm	ULOR	7%
Luminous efficacy	84 lm/W	Total flux	1858 lm
CCT	3000 K	Total power	22 W
CRI	80		



1 x LED			
Nominal lamp power	30 W	LOR	100%
Lamp flux	2599 lm	ULOR	7%
Luminous efficacy	87 lm/W	Total flux	2599 lm
CCT	3000 K	Total power	30 W
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 22-41 W
Appliance Class: II

Shape and measurements

Length: 23.62 in

Width: 23.62 in

Height: 1.90 in

Adjustability

Fixed

Protection

IP: 44