


Product data sheet

SMALL SIROCCO OPTIC - AREA LIGHT / BI-SYMMETRIC SINGLE SIDED
7241-H-5-672-XX
UNILAMP



Description SIROCCO is a family of floodlight, surface washer and area lighting. Two types of light distribution, asymmetric and bi-symmetric. Available with a range of mounting accessories including ground mount base, pole top mount, and wall/pole mounting arm. It is designed to operate with the high lumen output LED light source. Reflectors for SIROCCO have been engineered utilizing the latest technology and software for maximum performance. A calibrated aiming unit provides accuracy of light distribution on any surface or structure. SIROCCO is suitable to illuminate medium to large size objects or areas such as signage boards, building facades, parking lots, public parks, pedestrian, small streets and squares. Galvanized steel pole and anchor unit for concrete foundation are also available. SPEC • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • Anodized aluminium reflector. • Adjustable optic. • GFR PA6.6 Terminal block. • M16 cable gland or weather proof grommet. • Pole light and flood light pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED			
Nominal lamp power	76 W	LOR	100%
Lamp flux	9990 lm	Total flux	9990 lm
Luminous efficacy	131 lm/W	Total power	84 W
CCT	4000 K		
CRI	80		

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 4.13 in
Width: 7.29 in
Height: 15.93 in

Adjustability

Tiltable

Electric

System power: 84 W
Controller: DALI
Appliance Class: I

Protection

IP: 65
IK: 07