Product data sheet

ALPHABET FOCUS RECESSED LUMINAIRE, FULLY RECESSED ADJUSTABLE SPOTLIGHT AF2103001-33-40_(ALPHA-MIN)

SCHMITZ | WILA








alphabet focus LED 4000 K Recessed Luminaire, Light distribution direct Fully Recessed Adjustable Spotlight Product: AF2103001-33-40 Operating technology: independent driver required Light Technique highly precise lens technology (PLT) for beam angles, with focus unit for stepless fine adjustment Light module 361° rotatable, with integrated rotation stop tilt range from 0-30° variable beam angles 14° - 24° CRI > 90 constant colour temperature 4000 K lifetime 50.000 h (L70) Aluminium reflector (Al99.98), high-polished Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised ring thickness of only 2 mm for homogeneous appearance in the ceiling cover frame white, RAL 9016 Operating and assembly technology LED driver to be ordered separately Driver suitable for connection to central battery systems Quick installation due to 4-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 18 W Colour Rendering Index: 90 Colour Temperature: 4000 K Luminaire Luminous Flux: 360 Llm - 760 Llm System Efficiency: 38 Llm/W Half-peak Divergence 400 C 14° - 400 C 24° Number Luminaires LZ: 400 C 15 Connector: Screw Connector, 400 C 15 mm Installation Depth RD: 400 C 10 Length: 400 C 17 mm Width: 400 C 17 mm Cut-out length: 400 C 18 mm Cut-out width: 400 C 19 mm Cut-out width: 400 C 18 mm Installation Depth RD: 400 C 19 mm Total Weight: 400 C 11 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record AF2103001-400 C 19 mm NIN)

Light output 1



1 x General	service	incand	lescent	lamn
I A Octiciai	oci vioc	mound	COOCIIC	iuiip

Nominal lamp power	20 W
Lamp flux	360 lm
Luminous efficacy	18 lm/W
CCT	4000 K
CRI	90

LOR 100%
Total flux 360 lm
Total power 20 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 5.00 in Width: 5.00 in Height: 7.87 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 20 W Appliance Class: II

Protection

IP: 20