
Product data sheet


LIGHTING FOR ADMINISTRATIVE AND OFFICE BUILDINGS
V1-R4-00010-31HGS-5403640 GR070/C 2.0 588X588X50 MM IP54 30W 4000K OPAL MICROWAVE SENSOR
VARTON



IP 54 IK 02

LED luminaire solution for GRILIATO ceilings with IP54. Stainless steel housing with white powder coating. Application: administrative facilities For GRILIATO suspended ceilings with special rails. Can be fixed at the level of GRILIATO cells with a height of 30, 40 or 50 mm. Length: 588 Width: 588 Height/depth: 50 Input voltage (AC, 50Hz): 176...264 Power factor: 0,95 Ingress protection (IP): IP54 Impact resistance: IK02 Protection class: I AC frequency: 50 Flicker: 1 Climatic modification and category of placement: УХЛ4 https://www.varton.ru/products/ofisnoe-osveshchenie/varton-dlya-grilyato-gr-seriya-2-0/gr070-s-2-0-588kh588kh50-mm-ip54/svetodiodnyy-svetilnik-varton-gr070-c-2-0-588kh588kh50-mm-30-vt-4000-k-ip54-dlya-chistykh-pomeshchen_3/

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	3150 lm	Total flux	3150 lm
Luminous efficacy	105 lm/W	Total power	30 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.15 in
Width: 23.15 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 54
IK: 02