

Product data sheet


FLEXBAR SURFACE / SUSPENDED - 14W (10W/M) - SECONDARY STRAIGHT - 1400MM - UP & DOWNLIGHT - BLACK REF - ...
EFR14MSUB
THORLUX LIGHTING



IP
20


Flexbar is an elegant surface mounted or suspended linear luminaire ideal for a wide range of applications. The high performance lens technology provides well-controlled low glare lighting for optimum user comfort. Individual and continuous versions along with corner joints allow the lighting designer to be creative with their lighting layouts. Supreme efficiency (160.5 LL/cW) and 100,000 hour life ensures Flexbar has the performance to match its beauty. Applications: Offices, teaching spaces, meeting rooms, breakout areas, reception areas, circulation spaces and retail

Light output 1 (emergency)



1 x LED			
Nominal lamp power	14 W	LOR	100%
Lamp flux	2010 lm	Total flux	2010 lm
Luminous efficacy	126 lm/W	Total power	16 W
CCT	4000 K		
CRI	80		

Light output 2



1 x LED			
Nominal lamp power	14 W	LOR	100%
Lamp flux	2010 lm	ULOR	20%
Luminous efficacy	126 lm/W	Total flux	2010 lm
CCT	4000 K	Total power	16 W
CRI	80		

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 55.12 in

Width: 1.73 in

Height: 2.40 in

Adjustability

Fixed, Height adjustable

Electric

System power: 32 W

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20