


Product data sheet

SAFELITE 20M,MAINS,IP65,400LM,SLAVE,CG-S
SL2-M65J0JCGS
EATON EMERGENCY LIGHTING




- LED safety luminaire for all applications (Escape route, Anti-panic, Exit sign) • First fix base for ease of installation • High impact resistant (IK07) and high degree of protection (IP65) • Recessed mounting optional • Minimum service requirement due to high service life of the LEDs (up to 50,000 hours) • Shortened inspection effort due to CEWA GUARD technology • Automatic function monitoring of up to 20 luminaires per circuit • Reduced installation expenditure with STAR technology • Freely programmable mixed operation of the switching modes per luminaire in one circuit

Light output 1 (integrated)



Lamp type	LED	CCT	5700 K
Nominal lamp power	2.8 W	CRI	80
Total flux	400 lm	LOR	100%
Luminous efficacy	143 lm/W	Total power	2.8 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	5700 K
Nominal lamp power	2.8 W	CRI	80
Total flux	400 lm	LOR	100%
Luminous efficacy	143 lm/W	Total power	2.8 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 10.63 in

Width: 4.69 in

Height: 1.93 in

Adjustability

Fixed

Electric

System power: 5.6 W

Appliance Class: II

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 65

IK: 07