

Product data sheet

GONIA
611942.004.1
RZB




IP
65

IK
07

Series: GONIA Pole-top luminaire with classic design and modern LED technology. Luminaire body aluminium, arm cast aluminium with integrated wiring and stainless steel threaded inserts (seawater resistant powder-coated). With membrane valve as a standard to avoid condensed water. Refractor optics with multichip LED. Aluminium light insert with toughened glazing, powder coated. Asymmetrical light distribution for area lighting (P or C lighting classes). Pole attachment for 76 mm spigot. With stainless steel screws. Twist-lock and plug connector for quick replacement. 4 x 1.0 mm² connecting cable included, length 5.5 m. CityTouch-ready, luminaire can be fitted with CityTouch components if required. Please order reducer adapter for pole clamp D 60 mm separately. Colour: silver, matt (approx. RAL 9006) Diameter: 500 mm Height: 525 mm Lamp: LED System power: 24 W Rated luminous flux: 2150 lm Luminous efficiency: 90 lm/W Control gear: Converter, dimmable, DALI Protection class: II Type of protection: IP 65

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	70
Total flux	2150 lm	LOR	100%
Luminous efficacy	90 lm/W	ULOR	13%
		Total power	24 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 20.67 in

Diameter: 19.69 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 24 W

Protection

IP: 65

IK: 07