


# Product data sheet

MINIGRID IN TRIMLESS 2 93018  
100016 9310  
DELTA LIGHT




Luminaire, ceiling recessed (indoor use) from Deltalight, named MINIGRID IN TRIMLESS 2 93018, available in the colour(s): black-black, black-white, white-black, white-white. For recessed mounting, a rectangular opening (for installing a custom mounting kit) is needed and a min. depth for recessing of 85 mm. This luminaire is equipped with 2 x (LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 787-1089lm) with an optional driver, suitable for currents of 350mA to 500mA. Light distributor: reflector 18°.

## Light output 1




1 x LED			
Nominal lamp power	9 W	LOR	73%
Lamp flux	1089 lm	Total flux	792 lm
Luminous efficacy	121 lm/W	Total power	12 W
CCT	3000 K		
CRI	90		




1 x LED			
Nominal lamp power	6 W	LOR	73%
Lamp flux	787 lm	Total flux	573 lm
Luminous efficacy	131 lm/W	Total power	8 W
CCT	3000 K		
CRI	90		

## Light output 2



1 x LED			
Nominal lamp power	9 W	LOR	73%
Lamp flux	1089 lm	Total flux	792 lm
Luminous efficacy	121 lm/W	Total power	12 W
CCT	3000 K		
CRI	90		



**1 x LED**

Nominal lamp power	6 W	LOR	73%
Lamp flux	787 lm	Total flux	573 lm
Luminous efficacy	131 lm/W	Total power	8 W
CCT	3000 K		
CRI	90		

**Mounting mode**

Ceiling recessed

**Shape and measurements**

Length: 4.09 in  
Width: 8.15 in  
Height: 0.04 in

**Electric**

System power: 16-24 W  
Appliance Class: II

**Protection**

IP: 20  
Designation labels: CE