

# Product data sheet

2.5W 3000K 120°

L305-L301


MP LIGHTING



IP  
40

Application Interior directional in-grade light for lighting walls, columns, architectural features or landscape features. Applicable for mounting into floors, walls, ceilings or other surfaces where a non-obtrusive luminaire is required. Suitable for walk-over/ drive-over applications. IP Rating 40 Mounting Comes with flange which mounts to pre-installed standard 4" (102mm) octagonal box, 1-1/2" (38mm) deep minimum and 1/4" (6mm) setback from face of drywall. Can be wall or ceiling mounted. Electrical Powered by remote dimmable/ non-dimmable driver (sold separately). \*See website for recommended drivers \*Remote emergency driver / inverter options available. Consult factory. Power Consumption 1.5 Watt (at 350 mA, 1.0 Watt) 3.0 Watt (at 700 mA, 2.5 Watt) Light Output 1.0 Watt, 47~52lm 2.5 Watt, 75.2~79.4lm Warranty 5 years limited warranty Estimated useful life of LED is 50,000 hours. Material Solid anodized aluminum or stainless steel (316) with tempered glass lens, RoHS compliant. Weight 1.8lbs (0.816kg) base extra

## Light output 1



### 1 x LED

Nominal lamp power	2.5 W	LOR	68%
Lamp flux	75 lm	Total flux	51 lm
Luminous efficacy	20 lm/W	Total power	2.5 W
CCT	3000 K		
CRI	80		

## Mounting mode

Wall recessed

Electric

System power: 2.5 W

## Shape and measurements

Length: 2.20 in

Protection

Width: 0.08 in

IP: 40

Height: 2.20 in

## Adjustability

Fixed