


Product data sheet


2.5W 3000K 120°
L305-L301
MP LIGHTING



IP
40

Application Interior directional in-grade light for lighting walls, columns, architectural features or landscape features. Applicable for mounting into floors, walls, ceilings or other surfaces where a non-obtrusive luminaire is required. Suitable for walk-over/ drive-over applications. IP Rating 40 Mounting Comes with flange which mounts to pre-installed standard 4" (102mm) octagonal box, 1-1/2" (38mm) deep minimum and 1/4" (6mm) setback from face of drywall. Can be wall or ceiling mounted. Electrical Powered by remote dimmable/ non-dimmable driver (sold separately). *See website for recommended drivers *Remote emergency driver / inverter options available. Consult factory. Power Consumption 1.5 Watt (at 350 mA, 1.0 Watt) 3.0 Watt (at 700 mA, 2.5 Watt) Light Output 1.0 Watt, 47~52lm 2.5 Watt, 75.2~79.4lm Warranty 5 years limited warranty Estimated useful life of LED is 50,000 hours. Material Solid anodized aluminum or stainless steel (316) with tempered glass lens, RoHS compliant. Weight 1.8lbs (0.816kg) base extra

Light output 1



1 x LED			
Nominal lamp power	2.5 W	LOR	68%
Lamp flux	75 lm	Total flux	51 lm
Luminous efficacy	20 lm/W	Total power	2.5 W
CCT	3000 K		
CRI	80		

Mounting mode

Wall recessed

Shape and measurements

Length: 2.20 in
Width: 0.08 in
Height: 2.20 in

Adjustability

Fixed

Electric

System power: 2.5 W

Protection

IP: 40