


Product data sheet

3F LINDA LED LITE TR 1X12W L660
58852
3F FILIPPI



ILLUMINOTECHNICAL Luminous efficiency 100% (DLOR 96%, ULOR 4%). Initial luminous flux of the luminaire 2112 lm. Controlled symmetric distribution. Installation Interdistance Transv.D = 1.77 x hu - Long.D = 1.16 x hu. Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 20.5 - 21.4. Beam angle: 108° - 61°. Luminous efficacy 151 lm/W. Lifetime (L93/B10): 30000 h. (tq+25°C) Lifetime (L90/B10): 50000 h. (tq+25°C) Lifetime (L85/B10): 50000 h. (tq+35°C) Sudden decreased luminous flux after 50000 hours: 0% (C0). Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471). In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards. SOURCE Linear LED module 12W/840. Energy efficiency class (UE 2019/2020 - UE 2019/2015): D. CIE 13.3 Colour rendering index: CRI >80 (R9 <50%). IES TM-30 Fidelity Index: Rf = 84 Rg = 95. CCT nominal colour temperature 4000 K. Colour initial tolerance (MacAdam): SDCM 3. MECHANICAL Housing in transparent self-extinguishing V2 polycarbonate, UV stabilised, injection moulded. Ecologic anti-aging injected sealing gasket. Diffuser in self-extinguishing V2 polycarbonate, photo-engraved interior, UV stabilised, injection moulded with smooth outer surface, tamper-proof opening. Gear-holder reflector in hot-dip galvanised steel, painted with white polyester base. Snug fit safety snap-lock clips for diffuser mounting in stainless steel, screwdriver opening. Fixing brackets in stainless steel. Possibility for technicians to access the interior of the luminaire. Luminaire with limited surface temperature. - D - (EN 60598-2-24) Dimensions: 660x100 mm, height 100 mm. Weight 1.357 kg. IP66 protection degree. Mechanical strength to impacts IK10 (20 joule). Glow-wire test resistance 850°C. ELECTRICAL Halogen Free electronic wiring 230V-50/60Hz, power factor 0.95, THD <25%, constant output current, SELV, class I, 1 driver. Power of the luminaire 14 W. ENEC - CE. SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC. Ambient temperature from -20°C to +35°C. Temperature class T6 max 85°C. Relative humidity UR: <85%. INSTALLATION Ceiling / Suspended / Wall. All accessories dedicated to this product are available on the Catalog and on our website www.3F-Filippi.com. APPLICATIONS Suitable product for food production plants (HACCP), IFS (Food Version 6), BRC (GSFS Food Version 7). Dry, dusty indoor environments, subject to occasional water splashes. Environments: transit areas, parking lots. Environments where soft diffuse light is required for optimal visual comfort. Virtually shatterproof polycarbonate compatibly with the fumes / atmospheres that compromise the elasticity of plastic materials. Not suitable in environments where chlorine fumes, ligroin, hydrocarbon mixtures, mineral oil vapours or fumes of lubricating emulsions to cool down machine tools are present. Not suitable for installation on surfaces subject to important vibrations, exposed to weather conditions, on ropes or poles. Suitable for illumination of public car parks and parking grounds referred to DIN 67528:2018-04. WARNING Fixture not suitable for cold stores with an ambient temperature <0°C and/or relative humidity >85%. Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Light output 1



1 x LED			
Nominal lamp power	14 W	LOR	100%
Lamp flux	2112 lm	ULOR	4%
Luminous efficacy	151 lm/W	Total flux	2112 lm
CCT	4000 K	Total power	14 W
CRI	80		

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 25.98 in

Width: 3.94 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 14 W

Appliance Class: I

Protection

IP: 66