
Product data sheet

LUNA_ROUND_210_MV_LED_CHIP_26W_NEUTRAL
4667023_
PETRIDIS



Luna Round LED: Due to it's high system light output, Luna Round LED can replace even a downlight with 2x32W TC-Del lamps. This compact luminaire is ideal for applications where diffuse light is needed. Technical Features - Outer ring from die-cast aluminium, painted electrostatically in selected colour or plated. - Inner body from die-cast aluminium. - High pure aluminium reflectors anodized. - Crusiform louvre non-iridescent with parabolic blades made of pure aluminium. - Protection glass available in silkscreen TRD, sandblast SB or Mistlite. - Support to the ceiling with springs. - Pure light without IR/UV radiation. - Die cast aluminum heatsink anodized. - Efficient thermal management. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). - Connection for operation with Constant Current. Upon request: Available with highest colour rendering index (CRI)

Light output 1



1 x LED

Nominal lamp power	26 W	LOR	64%
Lamp flux	3995 lm	Total flux	2541 lm
Luminous efficacy	154 lm/W	Total power	26 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 6.30 in
Diameter: 8.27 in

Adjustability

Fixed

Design

Material impression: Aluminum, Plastic

Electric

System power: 26 W
Controller: Dimmable 1..10V, DALI
Appliance Class: II

Protection

IP: 43
Designation labels: CE, ENEC