



# Product data sheet

THOR B S 10L25 MAS 740 RGB R/S CL2 MPL  
96265403  
THORN LIGHTING



An elegant vandal resistant radially symmetric slim bollard with high performance optic. For Electronic, fixed output control gear. IP66 Electrical Class II. Column and Base: aluminium (EW AW 6060). Canopy: die-cast aluminium (EN AC 47100). Diffuser: Clear anti UV polycarbonate. Gear Box: polycarbonate. Canopy and Column colour: powder coated dark grey (close to RAL7043). RGB decorative lit band at the base of the head to be easily set at installation. Integral presence detector for on/off control. Ready to install prewired luminaire. Connection box required, to be ordered separately. Complete with 4000K LED Flange mounting: 4 x anchor bolts M14 (to be ordered separately), spacing: 150mm Dimensions: 160 x 160 x 1017 mm Total power: 11 W Weight: 7.9 kg

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3000 K |
| Nominal lamp power | 11 W    | CRI         | 70     |
| Total flux         | 873 lm  | LOR         | 100%   |
| Luminous efficacy  | 79 lm/W | ULOR        | 4%     |
|                    |         | Total power | 11 W   |

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 40.04 in

Diameter: 6.30 in

Weight: 7.9 kg

## Design

Material impression: Aluminum

## Electric

System power: 11 W

Voltage: 230 V AC

Appliance Class: II

## Protection

IP: 66

IK: 10

Designation labels: CE