
Product data sheet

FEMTOLINE 35 - PROFILE
391 00 00
DELTA LIGHT




391 00 00 FEMTOLINE 35 - PROFILE

Light output 1




1 x LED

Nominal lamp power	2 W	LOR	73%
Lamp flux	244 lm	Total flux	178 lm
Luminous efficacy	122 lm/W	Total power	2.4 W
CCT	4000 K		
CRI	90		




1 x LED

Nominal lamp power	2 W	LOR	73%
Lamp flux	244 lm	Total flux	178 lm
Luminous efficacy	122 lm/W	Total power	2.4 W
CCT	4000 K		
CRI	90		




1 x LED

Nominal lamp power	1.5 W	LOR	73%
Lamp flux	181 lm	Total flux	132 lm
Luminous efficacy	121 lm/W	Total power	1.8 W
CCT	4000 K		
CRI	90		




1 x LED

Nominal lamp power	1.5 W	LOR	73%
Lamp flux	181 lm	Total flux	132 lm
Luminous efficacy	121 lm/W	Total power	1.8 W
CCT	4000 K		
CRI	90		



1 x LED

Nominal lamp power	0.5 W	LOR	73%
Lamp flux	54 lm	Total flux	39 lm
Luminous efficacy	108 lm/W	Total power	0.6 W
CCT	4000 K		
CRI	90		



1 x LED

Nominal lamp power	0.5 W	LOR	73%
Lamp flux	54 lm	Total flux	39 lm
Luminous efficacy	108 lm/W	Total power	0.6 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted, Pendant, Floor mounted

Shape and measurements

Length: 3.94 in
Width: 0.83 in
Height: 1.38 in
Weight: 0.4 kg

Electric

System power: 0.6-2.4 W
Appliance Class: II

Protection

Designation labels: CE