## Product data sheet

VOLKMAR III (1-ARMED) 9.870.0187.00

LEIPZIGER LEUCHTEN








For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm, separately - Order pole for multi-bracket luminaire, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



1 x High pressure sodiun	n vapour lamp	
Nominal lamp power	50 W	
Lamp flux	3500 lm	
Luminous efficacy	31 lm/W	
CCT	2000 K	
CRI	25	



LOR

ULOR

Total flux

Total power



Pole top mounted

Shape and measurements

Height: 28.35 in Diameter: 16.14 in Electric

System power: 62-83 W

Protection

IP: 55

55%

15%

62 W

1912 lm