


Product data sheet

LED DOWNLIGHTS
V1-R0-00083-10000-4401640 DL-01 16 W 16W 4000K
VARTON



Classic dust-tight downlight. Paintable in any RAL color. Application: healthcare, offices, commercial spaces, hospitality (restaurants, hotels, coffee bars), retail spaces. Installation: recessed into plasterboard, stretch or suspended ceilings. Housing material: Aluminium Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Flicker, %: 5 Climatic modification and category of placement: YXJ4 Protection class: II Ingress protection (IP): IP54 Impact resistance: IK08 Mounting method: Built-in <https://www.varton.ru/products/daunlayty/dl-01/dl-01-16-vt/svetodiodnyy-svetilnik-varton-dl-01-kruglyy-vstraivaemyy-190x70-mm-16-vt-4000-k-ip54-ral9010-belyy-m/>

Light output 1



1 x LED			
Nominal lamp power	16 W	LOR	100%
Lamp flux	1600 lm	Total flux	1600 lm
Luminous efficacy	100 lm/W	Total power	16 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 2.76 in
Diameter: 7.48 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: Black

Electric

System power: 16 W
Ballast: ECG

Protection

IP: 54
IK: 08
Designation labels: CE

Other operating numbers

Ambient temperature range: 1...95°F