Product data sheet


FIL45 G2 SUR 1400 2800 930 TECH ASY WH
F42SF140MOTA930NW
LAMP



IP 20 IK 07

LAMP suspended or surface mounted structure FIL45 G2 SUR 1400. Manufactured from extruded aluminum with an 80% recycling rate, asymmetrical optic and black mat polycarbonate reflector TECH ULTRACONFORT to control light distribution and reduce glare UGR <15. Model for LED MID-POWER, colour temperature 3000K and IRC90. Electronic ON OFF gear included. IP20, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: 90.000 L80 B10. Available finishes: White, black and grey. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Light output 1



1 x LED

Nominal lamp power	19.4 W	LOR	100%
Lamp flux	1786 lm	Total flux	1783 lm
Luminous efficacy	92 lm/W	Total power	19.4 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 55.12 in
Width: 1.77 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 19.4 W
Appliance Class: I

Protection

IP: 20
IK: 07