


Product data sheet

CLARA VII (CLEAR ATTACHMENT)
9.767.1032.05
LEIPZIGER LEUCHTEN



For medium/high light requirements, mounting height 4.00 – 7.00 m. - Impact-resistant clear/opal polycarbonate attachment,UV- stabilized - High-pressure lamps with coated bulbs use reflector lamellae made of premium highest-grade aluminium, burnishid and anodized, for light guidance and glare limitation - Computer-optimized reflector system for high-pressure lamps with clear glass tubular bulbs ensures excellent illumination -Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on one block - Adapter jack connection -Available in any RAL or DB colour without surcharge - for post dia. 76mm; order post dia.76mm separately

Light output 1



| | | | |
|-----------------------|---------|-------------|---------|
| 1 x Metal halide lamp | | | |
| Nominal lamp power | 70 W | LOR | 55% |
| Lamp flux | 7200 lm | ULOR | 11% |
| Luminous efficacy | 45 lm/W | Total flux | 3981 lm |
| CCT | 3000 K | Total power | 89 W |
| CRI | 90 | | |

Mounting mode

Pole top mounted

Electric

System power: 89 W

Shape and measurements

Height: 27.56 in
Diameter: 29.92 in