


# Product data sheet

C90-S570 5000 830 OP  
GLAMOX



Light source LED 1400 - 24 000 lumen out Colour temperature 3000/4000 K, CRI Ra 80, MacAdams 3 Driver Electronic ballast (HF) or DALI. Driver life time up to 100.000 h/10 % (max failure) at Ta 25°C. Body material & colour White or grey powder coated aluminium body. Optics Opal (OP) or micro prismatic (MP) with dust cover on top. MP only available on 420, 570 and 870 version. Sensors This product is available with a PIR sensor type SPR-SEN with relay based ON/OFF switch or a PIR sensor wired for Corridor function type SPC-SEN. It is also available with a combined PIR and Constant Light sensor with integrated DALI Power supply type MPP-SEN or a slave PIR version type MPS-SEN. For more information see user manual for the respective sensor under “Download”. Emergency system Standard (S), Self test (ST) or DALI. 1h or 3h.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	39 W	CRI	80
Total flux	5003 lm	LOR	100%
Luminous efficacy	128 lm/W	ULOR	84%
		Total power	39 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 3.46 in

Diameter: 22.44 in

## Adjustability

Fixed

## Electric

System power: 39 W

## Protection

IP: 20