


# Product data sheet

ATLANTYK STRONG LED 1299 6640LM 4000K ACRYLIC (PMMA) IP65 GRAY  
090250.5L05.711.938  
LUG



Industrial luminaire for LED light sources, water-jet protected with an increased chemical resistance, dedicated to use in extreme environments. Mounting: directly on the ceiling, suspended, with mounting brackets (included) Body: polyester material reinforced with fibreglass Power: 220-240V 50/60Hz Lifetime (L80B10): 50 000 h Operating temperature range: -20°C ... +25°C Available on request: DIM 1..10V, DALI Additional equipment: stainless steel clips Warranty: 5 years Application: industrial facilities, warehouses, parking areas, laboratories, metro

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	53 W	CRI	108
Total flux	6640 lm	LOR	100%
Luminous efficacy	125 lm/W	ULOR	9%
		Total power	53 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 51.14 in  
Width: 3.35 in  
Height: 3.62 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray

## Electric

System power: 53 W  
Appliance Class: I

## Protection

IP: 65  
IK: 05