Product data sheet

LIGHTING FOR SPORTS FACILITIES

V1-P1-702X3-04R06-6542050 AIRQUB SPORT 280 W 420W 5000K TRANSPARENT DMX-RDM 90°

VARTON

IP 67 IK 01

High-power floodlight with a wide range of wattage and optics. Best lumens/mass/size ratio in its class of solutions. Material: Cast aluminum radiator, steel body parts, acrylic optic. Installation: Surface-mounted using an adjustable bracket. The mounting bracket has an angle of inclination 30° to the horizontal for comfortable aiming of the spotlight.Angle of rotation: 30° to 165° in 5° increment. Application: Outdoor areas. Industrial facilities. Sports lighting. Input voltage (AC, 50Hz), V: 90...305 AC frequency, Hz: 50 Input voltage (DC), V: 127...250 Flicker, %: 1 Climatic modification and category of placement: УХЛ1 Protection class: I Ingress protection (IP): IP67 Impact resistance: IK01 Power factor: 0,95 https://www.varton.ru/products/sportivnoe-osveshchenie/airqub-sport/airqub-sport-420-vt/svetodiodnyy-prozhektor-varton-airqub-sport-420-vt-5000-k-90-dmx-rdm/

Light output 1



1 x LED

Nominal lamp power	420 W	LOR	100%
Lamp flux	59500 lm	Total flux	59500 lm
Luminous efficacy	142 lm/W	Total power	420 W
CCT	5000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.15 in
Width: 19.92 in
Height: 16.46 in

Adjustability

Fixed

Electric

System power: 420 W

Protection

IP: 67
IK: 01