



Product data sheet

SYSTEM BATTEN LUMINAIRE TRAQ ICE M1500 25W 4150LM CRI > 80
2005.5053 - TRAQ ICE INS M1500 LED4150-840 WB WH ONF
REGENT



System batten luminaire Traq ICE m1500, for mounting on ICE mounting rail, with LED, system power: 25 W, standby power 0 W, luminous flux of luminaire 4150 lm, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 72'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, gear tray made of aluminium white similar to RAL 9016 with UV-resistant LED optics in polymethyl methacrylate (PMMA), wide beam, 1 integral control gear, ON/OFF, with halogen-free wiring, support profile and system components to be ordered separately protection class I, ingress protection IP20, impact strength: IK 06, for ambient temperatures 0 to +35 °C, this product contains a light source of energy efficiency class B and EPREL registration number: 1249134 L = 1481 mm, B = 65 mm, H = 66 mm

Light output 1



1 x LED			
Nominal lamp power	29 W	LOR	100%
Lamp flux	4150 lm	Total flux	4158 lm
Luminous efficacy	143 lm/W	Total power	25 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 58.31 in
Width: 2.56 in
Height: 0.94 in
Weight: 2.108 kg

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 25 W
Appliance Class: I

Protection

IP: 20
IK: 06