


# Product data sheet

STRIP-LIGHT LED  
451158.002.1  
RZB




IP  
20

IK  
02

Series: Strip-Light LED Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz "Very compact linear luminaire with rocker switch and MM mark;" "suitable for virtually all indoor lighting requirements. Housing: plastic, white;" "cover: plastic, prismatic; incorporated control gear and" LED. Optionally available cables for through-wiring "without tools; incl. 1,800mm power supply cable" and 160mm connecting cable, straight coupling and clips for wall and ceiling mounting "(which allow for very easy tool-free luminaire installation and maintenance);" max. 12 luminaires can be connected in series. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 836, B 23, H 37 Lamp: LED Life time: 25000 h (L70/B50) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark, MM Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 1250lm System power: 13W Beam Angle: 176°/113° Unified Glare Ratio: 25,8 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	80
Total flux	1250 lm	LOR	100%
Luminous efficacy	96 lm/W	ULOR	18%
		Total power	13 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 0.91 in  
Width: 32.91 in  
Height: 1.46 in

## Adjustability

Fixed

## Electric

System power: 13 W

## Protection

IP: 20  
IK: 02