## Product data sheet

MARCEL II (WALL FITTING) 9.842.2036.00

LEIPZIGER LEUCHTEN









For medium and high light requirements, mounting height 3.80 m. - Impact-resistant clear polycarbonate attachment, UV-stabilized, - Reflector lamellae made of premium highest-grade aluminium, burnished and anodized for light guidance and glare limitation - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x High pressure sodiur	n vapour lamp		
Nominal lamp power	50 W	LOR	
Lamp flux	3500 lm	ULOR	
Luminous efficacy	34 lm/W	Total flux	
CCT	2000 K	Total power	
CRI	25		



i x High pressure sodium	vapour iamp		
Nominal lamp power	70 W	LOR	60%
Lamp flux	5600 lm	ULOR	10%
Luminous efficacy	40 lm/W	Total flux	3346 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode

Wall mounted

Shape and measurements

Height: 20.08 in Diameter: 20.08 in Electric

System power: 62-83 W

Protection

IP: 55

60% 10% 2091 lm 62 W