Product data sheet

IMPS65 L68 LE3
IMPS EMERGENCY
DEXTRA



IP 65

Impervia Surface - 600 x 600, IP65 Surface mounted luminaire with steel housing, white powder painted metal body, ABS frame with polyurethane gasket and opal diffuser. Options: LE3 - Lithium Emergency (382 lumens output) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* H - High Frequency Dimming (Analogue 1-10v) C83 - CRI 80, 3000K TRS - tamper resistant screws

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	382 lm	LOR	100%
Luminous efficacy	127 lm/W	ULOR	20%
		Total power	3 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	40.8 W	CRI	80
Total flux	4757 lm	LOR	100%
Luminous efficacy	117 lm/W	ULOR	20%
		Total power	40.8 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.58 in
Width: 23.58 in
Height: 4.41 in

Adjustability

Fixed

Electric

System power: 43.8 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 65