
Product data sheet

VESPO LED 1161MM LS2 4800LM PRM IP44 830 (34W)
643538
LENA LIGHTING



643538 VESPO LED 1161mm LS2 4800lm PRM IP44 830 (34W) Surface mounted luminaire made of powder coated white steel with prismatic or prismatic mat PC diffuser providing soft & uniform light. Equipped with LED modules with high luminous efficacy and SDCM <3. The luminaire in standard version has a 5 pole terminal block, that enables quick through-wiring, and strain relief.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	35.8 W	CRI	80
Total flux	4800 lm	LOR	100%
Luminous efficacy	134 lm/W	Total power	35.8 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 45.71 in
Width: 4.88 in
Height: 2.36 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: White

Electric

System power: 35.8 W
Ballast: ECG
Suitable for feed-through wiring
Appliance Class: I

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor

Protection

IP: 44
IK: 07
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F