


Product data sheet

LESS IS MORE 50
312317.002.1.76
RZB




IP
20

IK
03

Series: LESS IS MORE 50 Linear pendant luminaire for aesthetically sophisticated lighting. Housing made of extruded aluminium profile, powder-coated. End cap made of aluminium powder-coated. Canopy made of aluminium, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Direct 65%, indirect 35% light emission. Suitable for pendant. 2-point steel cable suspension freely positionable and infinitely height-adjustable. Special lengths available on request. LED unit with integrated converter interchangeable and removable. Suitable for through-wiring. With sensors or as a safety luminaire on request. Colour: traffic white, matt (RAL 9016) Length: 847 mm Width: 57 mm Height: 75 mm Suspension length: 500-2000 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 Light source: LED Socket lamp2: Without base Colour temperature: 4000K System power: 34 W Rated luminous flux: 4000 lm Beam angle Down: 104° / 107° Luminous efficiency: 118 lm/W Control gear: Converter, dimmable, DALI Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	34 W	CRI	80
Total flux	4000 lm	LOR	62%
Luminous efficacy	118 lm/W	ULOR	18%
		Total power	34 W

Mounting mode

Pendant

Electric

System power: 34 W

Shape and measurements

Length: 2.24 in
Width: 33.35 in
Height: 2.95 in

Protection

IP: 20
IK: 03

Adjustability

Fixed

Design

Color of housing: White