Product data sheet


WASHER GO MINI AC 50W 2700K 12D ON OFF
DL26PLN100425
TRAXON



IP 65 IK 07

Quick installation and self-locking waterproof connectors on all data lines and DC line DMX Control and On/Off options DMX addressing with the TX Smart Addresser IP66 and suitable for Coastal Environments IK07 ANSI 3G Vibration Rating Color Options RGBW (W=4000K), 2700K, 3000K, 4000K, 5700K, 6500K Standard RGB, DW (2700K+5700K) Optional Size/Wattage Options Micro for 25W DC24V Mini for 50W AC Midi for 100W AC Maxi for 150W AC Lens Options Certifications & Approbations Can't find what you are looking for? Contact us now Do you need a custom product? Inquire about custom options Looking for control options? Learn more about e:cue controls

Light output 1



1 x LED

Nominal lamp power	50 W	LOR	100%
Lamp flux	3750 lm	Total flux	3750 lm
Luminous efficacy	75 lm/W	Total power	50 W
CCT	2700 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 8.46 in
Diameter: 8.62 in

Adjustability

Rotatable, Tiltable

Electric

System power: 50 W

Protection

IP: 65
IK: 07