Product data sheet

URBINO TWILIGHT LED 36W 4300LM 5700K IP66 O5 - FOR RESIDENTIAL AREA ROADS GRAY I
130222.5L141.041.986


LUG



IP 66 IK 08

Professional streetlight luminaire for LED light sources. Luminaire with twilight sensor. High efficacy to 131 lm/W Mounting: on pillar ø60/76mm, on outriggers ø60/76mm Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.054 m² Power supply efficiency >95% Power: 220-240V 50/60Hz Lifetime (L90B10): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, knife switch, 10kV surge protection, NTC, access to the driver chamber without the use of tools. Additional information: tilt adjustment: -15° to +15° (every 5°). Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: express roads, local roads, town roads, residential area roads, pedestrian crossings, area lighting, avenues, promenade, cycle paths. Type of optics: O5 - for residential area roads

Light output 1 (integrated)



Lamp type	LED	CCT	5700 K
Nominal lamp power	36 W	CRI	70
Total flux	4300 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	36 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.65 in
Width: 9.84 in
Height: 7.68 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 36 W
Appliance Class: I

Integrated sensors

Integrated sensors: Daylight sensor

Protection

IP: 66
IK: 08