


Product data sheet

PURE 3 SPOT TRACK
09.1918/MASTERLINE111/60W/8°24°48°
FLOS




Luminaire for three-phase electric track installation. For very low voltage halogen lamps or standar and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double teflon insulation.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	60 W	Socket	G5.3
Lamp flux	1190 lm	LOR	100%
Luminous efficacy	20 lm/W	Total flux	1189 lm
CCT	3000 K	Total power	60 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	60 W	Socket	G5.3
Lamp flux	1420 lm	LOR	100%
Luminous efficacy	24 lm/W	Total flux	1418 lm
CCT	3000 K	Total power	60 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	60 W	Socket	G5.3
Lamp flux	1400 lm	LOR	99%
Luminous efficacy	23 lm/W	Total flux	1389 lm
CCT	3000 K	Total power	60 W
CRI	99		

Mounting mode

Ceiling mounted

Electric

System power: 60 W
Appliance Class: I

Shape and measurements

Length: 1.69 in

Width: 5.63 in

Height: 6.22 in

Adjustability

Free

Protection

IP: 20