


Product data sheet

PAN RTI M600 25W U19C90 DL3K
40150DLO
BEGHELLI



TECHNICAL FEATURES: indoor lighting fixture with LED technology, with direct/indirect lighting. For recessed in false ceilings module 600 with visible structure or 30x120. provided with LED Driver DALI with high energy saving DEGREE OF PROTECTION: IP40 DEGREE OF IMPACT PROTECTION: IK05 (0.7J) OPERATING TEMPERATURE: -20÷40°C STRUCTURE In pre-zincd sheet painted with polyester powders White RAL 9003 OPTICS: RTI: total internal reflection. High transmittance PMMA multi-lenticular lens with glare control. Product suitable for installation in environments with video windows (UNI-EN12464-1). LED SOURCE: Integrated LED modules: 4000K, 3000K or 6000K Ra>90; 3SDCM. LED modules are dissipated from the structure. DRIVER: Built in. Led Driver DALI. DIRECT current output. Constant luminous flux as the supply voltage increases. Protection against network surges. Reliability of the power system: MTBF >80000h. INSTALLATION: Suitable for installation on normally flammable surfaces, in module 600 false ceilings with visible structure, resting on the side by side. Ceiling and suspension with special accessories

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	24 W	CRI	90
Total flux	3230 lm	LOR	100%
Luminous efficacy	135 lm/W	Total power	24 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.43 in
Width: 23.43 in
Height: 0.39 in

Adjustability

Fixed

Design

Color of housing: White
Designer: Parmeggiani.G

Glare protection

Glare protection: UGR < 19

Electric

System power: 24 W
Ballast: ECG
Controller: DALI
Appliance Class: I

Protection

IP: 20
IK: 05
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -4...104°F