

Product data sheet


STELLA P IV DA LED (OPTIC 058)
6.628.8107.65058-3
LEIPZIGER LEUCHTEN



IP
65

• STELLA P IV: cap made of aluminium and tube made of hot-dip galvanised steel; powder coated • STELLA P I, I/13, IV/13; XXIII, XXIII/13: cap and tube made of aluminium; powder coated • glazing made of PMMA RESIST, clear, high-impact resistant • incl. cable junction box: incl. cable until the cable junction box for max. 2 cables up to 5x16mm²/ 3 cables up to 5x10mm² • with flange plate to be screwed on a concrete foundation on site or on an additional bolt-on root • to be ordered separately: bolt-on root (G240/500 for ø 170mm; G300/500 for ø 200mm; G330/500 for ø 230mm) with screws, accessory ring (Z248/1 for ø 170mm; Z305/2 for ø 200mm; Z338 for ø 230mm), back light shield for no glare on the rear side

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	8 W	CRI	70
Total flux	1072 lm	LOR	100%
Luminous efficacy	134 lm/W	Total power	8 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 42.52 in
Diameter: 6.69 in
Weight: 22.3 kg

Adjustability

Fixed

Electric

System power: 8 W

Protection

IP: 65