


# Product data sheet

UNISTREET GEN2 BGP284 T25 1 XLED420-4S/740 DRXN0  
BGP281  
PHILIPS



The easy way to ledify your road lighting – UniStreet gen2 Designed for large-scale ledification projects, the UniStreet gen2 is the ideal 1:1 luminaire replacement for municipalities. Thanks to its high efficiency and low initial cost, the UniStreet gen2 luminaire enables a fast payback and significant savings in terms of energy consumption within a short period of time. The ease of installation and maintenance is enabled by the Philips Service tag and the Philips SR (System Ready) socket makes it future-ready and you can pair this luminaire with lighting control and software applications such as Interact City. Available with a number of different optics and lumen packages that can even be tuned further to fit exact project requirements, UniStreet gen2 is a true point-to-point replacement solution for conventional light sources. The compact luminaire, using high-quality materials is also easy to dismantle and recycle at the end of its lifetime.

## Light output 1



|                    |          |             |          |
|--------------------|----------|-------------|----------|
| 1 x LED            |          |             |          |
| Nominal lamp power | 245 W    | LOR         | 83%      |
| Lamp flux          | 42000 lm | Total flux  | 35001 lm |
| Luminous efficacy  | 143 lm/W | Total power | 245 W    |
| CCT                | 4000 K   |             |          |
| CRI                | 70       |             |          |

## Mounting mode

Pole top mounted

## Electric

System power: 245 W

## Shape and measurements

Length: 32.01 in

Width: 13.39 in

Height: 5.98 in