


Product data sheet

MULTIDIR EVO SMALL DOUBLE RECESSED TRIM


AU13-P8V9F10U14

LEDSC4




LedsC4 Multidir Evo Small Double Recessed Trim AU13-P8V9F10U14V1 Downlight for indoor use. Adjustable light source. Structure material: Aluminium. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Transparent. Warranty: 5 Years. Product net weight (Kg): 1.66 Product length (mm): 220 Product width or diameter (mm): 120 Product height (mm): 88 Ø of the hole for recessing (mm): 210x110 Permitted ceiling thickness: 0-20 Class 2. IP: IP54. LED. No. of lampholders or LEDs: 1. LED brand: CREE. Driver brand: VOSSLOH-SCHWABE. Maximum power of light source: 17.3W. Colour temperature: 2700K. Colour rendering index: 92. MacAdam Steps: 2. Hours of life: 50.000h L80B20. UGR: 22.3. Photobiological risk: RG1. % de Flickering: <5%. Real flux (lm): 2082. Real lm/W: 105. Voltage / frequency range: 100-240/50-60Hz. Voltage: 33.7. Equipment included: Yes. Total power: 19.8. Power factor: NULL. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED


Nominal lamp power	9.1 W	LOR	100%
Lamp flux	1041 lm	Total flux	1041 lm
Luminous efficacy	114 lm/W	Total power	9.1 W
CCT	2700 K		
CRI	90		



1 x LED


Nominal lamp power	9.1 W	LOR	100%
Lamp flux	1041 lm	Total flux	1041 lm
Luminous efficacy	114 lm/W	Total power	9.1 W
CCT	2700 K		
CRI	90		

Light output 2



1 x LED

Nominal lamp power	9.1 W	LOR	100%
Lamp flux	964 lm	Total flux	964 lm
Luminous efficacy	106 lm/W	Total power	9.1 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	9.1 W	LOR	100%
Lamp flux	964 lm	Total flux	964 lm
Luminous efficacy	106 lm/W	Total power	9.1 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 8.66 in

Width: 4.72 in

Height: 0.12 in

Adjustability

Fixed

Electric

System power: 18.2 W

Appliance Class: II

Protection

IP: 54