


# Product data sheet

RESCLITE C ANTIPANIC AD E3D WH  
42180403  
ZUMTOBEL



LED Safety luminaire for anti-panic lighting with min. 0.5 lx as specified in EN 1838; surface mounted; Luminaire with local battery supply for 3 hr. emergency lighting in maintained or non-maintained mode, with automatic test (auto-test) via the luminaire, optional central monitoring via DALI, display of luminaire status via status LED; room height 2.2 to 5 m; high power LED, cool white; optimum thermal management via heat sink; lens made of polycarbonate (PC); luminaire housing made of die-cast aluminium in powder coated white finish, RAL 9016; luminaire can be installed quickly without tools; tool-free maintenance; through-wiring plug-in terminals for wire cross-sections up to 2.5 mm²; luminaire total power: 4.5 W; power supply: 230V AC; rotary switch for mechanical address-setting; degree of protection: IP40, class of protection: SC1; Impact strength: IK09; non-maintained and maintained mode possible, Maintained mode: +5°C to +30°C, Non-maintained mode: +5°C to +35°C; Dimensions: 146 x 146 x 37 mm; weight: 0.71 kg; Luminaire wired with halogen-free leads

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.5 W	CRI	99
Total flux	152 lm	LOR	100%
Luminous efficacy	34 lm/W	Total power	4.5 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 5.75 in  
Width: 5.75 in  
Height: 1.46 in  
Weight: 0.7 kg

## Design

Material impression: Aluminum  
Color of housing: White

## Electric

System power: 4.5 W  
Voltage: 220-240 V AC  
Appliance Class: I

## Protection

IP: 40  
IK: 09  
Designation labels: CE, ENEC