Product data sheet

TRAFFIK LED 36W 4550LM 4000K IP66 O28 - FOR EXPRESS ROADS GRAY I
130292.5L021.020
LUG



IP 66 IK 08

Professional streetlight luminaire for LED light sources. Mounting: on outriggers ø60/48mm Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.033 m². Power: 220-240V 50/60Hz Available on request: DIM 1..10V, LLOC, twilight sensor, 10kV surge protection, NTC Other remarks: the pole and boom are not part of the luminaire; luminaire available in protection class I and II Warranty: 5 years Application: local roads, express roads, town roads, residential area roads, area lighting, avenues, promenade, parking areas Type of optics: O28 - for express roads

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	36 W	CRI	70
Total flux	4550 lm	LOR	100%
Luminous efficacy	126 lm/W	Total power	36 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 19.88 in
Width: 9.06 in
Height: 3.15 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 36 W
Appliance Class: I

Protection

IP: 66
IK: 08