


Product data sheet

BTECSE L30
BTEC SECURE
DEXTRA



Btec Secure Downlighter - IP65, IK10, Recessed downlighter with spun aluminium housing, spring steel retaining clips and high transmission polycarbonate diffuser. When installed with anti-pick mastic to seal the luminaire to the mounting surface the BTEC Secure complies with ligature resistant requirements of the Department of Health Environmental Design Guide, Adult Medium Secure Services. Lighting control options: S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) H - High Frequency Dimming (Analogue 1-10v) RLI - Reacta-Link, Wireless Enabled Luminaire RC - Reacta-Control, Wireless Enabled Luminaire Emergency options: LE3 - Lithium Emergency LS3 - Lithium Selftest LA3 - Lithium Autotest

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19.3 W	CRI	80
Total flux	2450 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	19.3 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 2.80 in
Diameter: 8.74 in

Adjustability

Fixed

Electric

System power: 19.3 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor, Presence sensor

Protection

IP: 65
IK: 10
Resistant to impact of balls
Designation labels: CE