Product data sheet

LIGHT SNIPER ROUND

03.4655/HI PAR 51/35W/GX10/10°25°40° FLOS



FLOS 23


1 x Metal halide lamp Nominal lamp power


High performance luminaires for embedded installation for halogen lamps with dichroic reflector, metal halide reflector or LED lamps. They offer a high comfort due to the back visual position of light source. Body of the luminaire made of two bodies of injected aluminium. Round front ring made of steel sheet 1mm thick with white matt finish. It incorporates shielded cones made in zamak injection in three sets: black, matt gold and chrome. Fixed, tilt and wall-washers versions. Spreading lens made in opal tempered glass in halogen fixed and tilt versions. In wall-washer versions a distribution lens made of borosilicate is incorporated.


35 W

Socket

Light output 1







2100 lm LOR 47% Lamp flux Luminous efficacy 28 lm/W Total flux 981 lm CCT 3000 K Total power 35 W CRI 84 1 x Metal halide lamp Nominal lamp power 35 W Socket Gx10 Lamp flux 2100 lm LOR 42% Luminous efficacy 25 lm/W Total flux 890 lm CCT 3000 K Total power 35 W CRI 84 1 x Metal halide lamp Nominal lamp power 35 W Socket Gx10 Lamp flux 2100 lm LOR 46% 28 lm/W Luminous efficacy Total flux 968 lm CCT 3000 K 35 W Total power CRI 84

Mounting mode

Ceiling recessed

Electric System power: 35 W

Created by luminaires.dialux.com (16 May, 2024) Gx10

Shape and measurements

Height: 6.50 in Diameter: 3.94 in

Adjustability

Fixed

Protection

IP: 23