
Product data sheet

M26L - HEDRA 93008 DIM5
23251 9315
DELTA LIGHT




Luminaire, low voltage systems low voltage system mounted (indoor use) from Deltalight, named M26L - HEDRA 93008 DIM5, available in the colour(s): black bronze, gold coloured. This luminaire can be used with the following 48V magnetic lighting system(s): SHIFTLINE M26L - PROFILE. This luminaire is equipped with LED array 5,7W / CRI>90 (R9: 55) / 3000K / 519lm with build-in converter to operate on a voltage of 48V-DC. Dimming protocol: DALI. Light distributor: lens 8°.

Light output 1




1 x LED

Nominal lamp power	6 W	LOR	73%
Lamp flux	519 lm	Total flux	378 lm
Luminous efficacy	86 lm/W	Total power	6 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	6 W	LOR	73%
Lamp flux	519 lm	Total flux	378 lm
Luminous efficacy	86 lm/W	Total power	6 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	6 W	LOR	73%
Lamp flux	519 lm	Total flux	378 lm
Luminous efficacy	86 lm/W	Total power	6 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	6 W	LOR	73%
Lamp flux	519 lm	Total flux	378 lm
Luminous efficacy	86 lm/W	Total power	6 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	6 W	LOR	73%
Lamp flux	519 lm	Total flux	378 lm
Luminous efficacy	86 lm/W	Total power	6 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	6 W	LOR	73%
Lamp flux	519 lm	Total flux	378 lm
Luminous efficacy	86 lm/W	Total power	6 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	6 W	LOR	73%
Lamp flux	519 lm	Total flux	378 lm
Luminous efficacy	86 lm/W	Total power	6 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	6 W	LOR	73%
Lamp flux	519 lm	Total flux	378 lm
Luminous efficacy	86 lm/W	Total power	6 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

Shape and measurements

Length: 0.79 in
Width: 6.69 in
Height: 0.04 in

Electric

System power: 6 W
Appliance Class: II

Protection

IP: 20
Designation labels: CE