# Product data sheet

DEFINE LED WALL MOUNT LUMINAIRE
S125DIW-S375D770U935-4F0-1E-UDD-D
COOPER LIGHTING



IP 47

Wall Mount Slot family in 2", 3", 4" and 5" housing sizes, Specifiable to the nearest 1', Multiple lensing options: flush satin, drop, regressed and asymmetric, Multiple lumen packages, 0-10V dimming standard; DALI dimming available, 2700K, 3000K, 3500K, 4000K & 5000K correlated color temperatures, VividTune CCT tuning options from 3000K–5000K or 2700K-6500K, Integral Wavelinx and Stand-alone sensors available, Customizable in-wall, in-ceiling and wall-to-ceiling corners available, DLC listed configurations available

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3500 K |
| Nominal lamp power | 30.4 W | CRI | 90 |
| Total flux | 3902 lm | LOR | 100% |
| Luminous efficacy | 128 lm/W | ULOR | 70% |
| | | Total power | 30.4 W |

### Mounting mode

Wall mounted

### Shape and measurements

Length: 48.00 in
Width: 5.00 in
Height: 1.00 in

### Adjustability

Fixed

### Electric

System power: 30.4 W

### Protection

IP: 47