


# Product data sheet

SL629AB PRISM S/A 31W 830 DALI WH-RAL9016  
8629661406310  
PERFORMANCE IN LIGHTING



LED surface-mount luminaire for interior, comprising: Housing made of steel sheet, die-cast aluminium end caps, powder painted / Prismatic cover for efficient light diffusion, glare reduction and a high level of uniformity / Direct light distribution / LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover / Colour rendering index Ra > 80 / Colour tolerance according to MacAdam = 3 SDCM / Dimmable via TouchDIM / Light engine can be replaced by means of a slide-in mechanism / UGR <19 for all luminosities / VDU application suitable acc. to EN 12464-1 (see table) / Special colour versions available upon request

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 31 W     | CRI         | 80     |
| Total flux         | 3882 lm  | LOR         | 100%   |
| Luminous efficacy  | 125 lm/W | ULOR        | 5%     |
|                    |          | Total power | 31 W   |

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 60.79 in  
Width: 10.63 in  
Height: 1.18 in

## Design

Color of housing: White

## Electric

System power: 31 W  
Appliance Class: I

## Protection

IP: 20  
IK: 07